



PO BOX 4625, Auburn, CA 95604 USA
 Telephone 530 613 2150
[Email sales@dieselcraft.com](mailto:sales@dieselcraft.com)
www.dieselcraft.com

Model 5x24 Fuel Water Separator / Purifier

For Stationary Diesel Pumps, Generators and Equipment with Engines from to 1300 Horse Power or Transfer Pumps to 8 GPM

The Dieselcraft Fuel Purifier is a simple one step unit that removes 99% of the water and 95 to 98% of heavy particles. Unlike all other products on the market, the Dieselcraft Fuel Purifier performs its function without the use of a replaceable, changeable or cleanable filter element. This is the ONLY unit with a bed of activated alumina to help remove water and contamination. Removing the contamination immediately before the fuel enters the engine's fuel system, the Dieselcraft Fuel Purifier delivers cleaner fuel, greatly reduces filter clogging by reducing bacterial growth and therefore extending maintenance intervals.

All units include water sensor.

Product	Universal Fuel Purifier
Model	5x24 ABS
Maximum Flow	8 GPM, 30 LPM
In and Out couplings	1 inch NPT Forged Steel
Top Port	1/2 inch NPT
Drain Port	1/2 inch NPT
Sensor Port	1/8 inch NPT
Width / Diameter	5 inches, 127 MM
Gross Weight	20 pounds, 44 kilos
Finish	Epoxy Powder Coat Grey Custom colors available
Options	5" Adjustable Tripod Mount Welded Legs Stainless Steel Mounting Strap with Sensor Mount



Designed in accordance with ASME Section VIII DIV1, 2015 ED Rules

Design Pressure: 150 PSIG

Hydrotest Pressure: 195 PSIG

Design Temp: 300° F

MDMT: -20° F @ 150 PSIG

Corrosion Allowance: None

Heat Treatment: None (UW-40)

Radiography: None (UW-12)

